## M-283 CoolBLUE®

# **Product Specification For Inductive Common Mode Choke Components**

<u>'</u>				· · · · · · · · · · · · · · · · · · ·		
PS Index	01	Magnetec A/N	12511	Revision #	DATE	Alteration
PS Revision	02	Type:		01/01	2010/03/10	INITIAL ISSUE
				01/02	2014/11/14	100KHz lower limit defined
Core Material: Nanoperm®						

## **Mechanical Specification**

#### Part Number: M-283

Nominal Core Dimensions:

3.15 x 2.48 x 1.18 inch (80 x 63 x 30 mm)

Finished Core Dimensions:

OD1  $\leq$  3.98 inch (101mm) OD2  $\leq$  2.44 inch (62.0mm) ID1  $\geq$  2.68 inch (68.0mm) ID2  $\geq$  1.10 inch (28.0mm) H  $\leq$  1.46 inch (37.0mm) R<sub>1</sub> = 31.1mm : R<sub>2</sub> = 13.9mm

 $ext{le} = 22.36 \text{ cm}$   $ext{A} = 1.86 \text{ cm}^2$ 

Currie Temp = 1,112°F (600 °C) RTI Temp (0.81) = 248°F (120°C) MAGNETEC M-283-01 YM

R1

R2

ID1

OD1

H

Marking: M-283-01 YM: "-01" = Index; "YM" = Year/Month

Packing: 12 pc per layer, 5 layers/box; PU=60 pcs

#### **Electrical Core Performance**

Permea	Maximum Asymmetric				
l	Measured Value	Measurement Limits	Frequency	-en	Current I <sub>sat</sub> *
Inspection Value	$A_{\ell}$ (uH/N <sup>2</sup> )	24.1 - 48.2	10 KHz		(Sum Peak Current)
	A <sub>e</sub> (uH/N²)	12 min	100 KHz	50	6.0 A

\*Saturation Current Isat of NANOPERM®: Peak value of the exiting current when the initial inductance level is dropped to 10 per cent. Saturation behaviour is dependant on frequency, signal shape and leakage field. The current value is a calculated value for design help only and cannot be guaranteed. Isat is calculated @ B = 1.0 T - µ<sub>nom</sub> - N = 1.

Core Finishing						
Туре:	BLUE Case	Case material:	Zytel FR70G25 V0 NNC10 with RAL 5012 Blue Pigment			
Case UL file Number:	E41938	Voltage Breakdown:	2,500 volts rms between two copper wires on the core			

Magnetec GmbH certifies their manufacturing and quality processes meets all requirements of IEC Part 1: General Specification for "Fixed Inductors For Electromagnetic Interference Suppression", IEC 60938-1:1999 + A1:2006. This International Standard is used in lieu of requirements/documents pertaining to UL, CE, CSA, DIN and other individual agencies.

Magnetec GmbH certifies the product described herein is in compliance with the Directive 2011/65/EU of the European Parliament and of the council of 8 June, 2011 on the Restriction of the use of Certain Hazardous Substances in Electrical and Electronic Equipment (RoHS2 Directive)

### MH&W International Corp

Phone 201-891-8800 Email: sales@mhw-intl.com

#### MAGNETEC GmbH

Industriestrasse 7, D-63505 Langenselbold