

FORM Identifier: F 108 Revision: 03 Page: 1/1	Product specification for inductive components	
---	---	--



Client:	MAGNETEC GmbH	Magnetec P/N:	M-310	Magnetec A/N:	12369
Client's P/N:	/	PS Index:	02	PS Revision:	02
Subject:	WANDLER			Type:	E

1. Mechanical Outline	
Nominal core dimensions: 40,0 x 35,0 x 5,0 Finished product dimensions: OD ≤ 42,5 ID ≥ 31,8 H ≤ 7,5 [dimensions] = mm	

2. Core data			
Core material:	NANOPERM®	$L_{Fe} = 11,76 \text{ cm}$	$A_{Fe} = 0,09 \text{ cm}^2$
Nominal values:	Permeability level	@ frequency	@ H_{max}
	30 000	10 kHz	3,6 mA/cm

3. Inspection values				
	Measured value	Measurement limits	Frequency	Ieff x N [mA x turn]
	AL [μH]	2,1 - 4,2	10 kHz	30

4. Core finishing	
Type:	Cased
Marking:	MAGNETEC M-310-02 YM
Packaging:	24 pcs. per layer; 9 layers per carton box; PU = 216 pcs.

5. Comments:	
	☒ Date code (YM) on marking acc. to IEC 62 5.1; YM = production year and month ☒ RoHS compliant acc. to Directive 2002/95/EC

Index / Revision	Alteration	Date
02 / 01	Product Specification	05.10.2006
02 / 02	Packaging: PU = 216 pcs.	06.12.2006

Created:	A. Kovách	Approved (Techn):	F. Zámbořszky	Approved (Quality):	V. Káposztás	Released:	F. Rauscher
	06.12.2006		21.12.2006		22.12.2006		22.12.2006